



- 4.500 Nm maximum torque
- Planetary gear brings high load capacity
- Torque multiplication factor up to 26:1
- 1 year warranty, Origin: Taiwan
- Multiplication accuracy $\pm 5\%$
- Special coatings against corrosive environment
- Chromium-molybdenum alloy steel
- Input: 3/4" or 1/2" - Output: 3/4" or 1"
- Each tool is supplied with 2 reaction arms
- Easily to handle with carry case
- Robust design for heavy industries
- Wide technical support and spare part capability
- Trade Mark: TorcPLUS®

Code #	Max. Torque Nm	Gear Ratio -	Input Square inch	Output Square inch	Planetary Type Single/Double	Weight kg
TW-416	1.500	5:1	1/2"	3/4"	Single	6,48
TW-418	1.500	5:1	1/2"	1"	Single	6,48
TW-618	2.700	5:1	3/4"	1"	Single	6,48
TW-428-01	3.000	15,5:1	1/2"	1"	Double	11,5
TW-428-02	4.500	26:1	1/2"	1"	Double	13

TW-416 / 418 / 618



Input Torque Nm	Output Torque Nm	Gear Ratio -
300	1.500	5:1
300	1.500	5:1
540	2.700	5:1

TW-428-01 / 02



Input Torque Nm	Output Torque Nm	Gear Ratio -
200	3.000	15,5:1
180	4.500	26:1

* TW-428-01 and TW-428-02 models have anti-backlash mechanism for safety concern and comfortable operation.